

Ringlock System Scaffolding Double-locking Joints EN12810 & EN12811 Max Height ≤30m

Our Product Introduction

for more products please visit us on bythaiscaffold.com

Basic Information

- Place of Origin: China
- Brand Name: Bythai
- Model Number: BT03



Product Specification

- Safety Factor: ≥ 4
- Standard: EN12810 & EN12811
- Components: Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.
- Surface Treatment: Hot-dip Galvanized
- Weight: $\leq 30\text{kg/m}^2$
- Max Height: $\leq 30\text{m}$
- Horizontal Adjustment: $\leq \pm 3^\circ$
- Warranty: 2 Years
- Highlight: **scaffolding ringlock system,
horizontal ringlock system scaffolding**

Product Description

Product Description:

The Ringlock System Scaffolding is an ideal solution for fast and efficient scaffolding construction. It features a unique interlocking system, allowing for a secure and safe installation. The system offers high stability and flexibility, with a horizontal adjustment of $\leq \pm 3^\circ$, a weight of $\leq 30\text{kg/m}^2$, and a horizontal load capacity of $\geq 15\text{KN}$. Additionally, the Ringlock System Scaffolding is hot-dip galvanized to protect against corrosion and other environmental hazards, ensuring a long service life. Furthermore, the system is designed for maximum safety, with a safety factor of ≥ 4 . The Ringlock System Scaffolding is an easy and reliable solution for all your scaffolding needs.

Features:

Product Name: Ringlock System Scaffolding

Joints: Double-locking

Horizontal Load Capacity: $\geq 15\text{KN}$

Size: 48.3mm

Material: Q235 Steel

Safety Factor: ≥ 4

Technical Parameters:

Attribute	Value
Joints	Double-locking
Safety Factor	≥ 4
Surface Treatment	Hot-dip Galvanized
Components	Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.
Vertical Load Capacity	$\geq 45\text{KN}$
Weight	$\leq 30\text{kg/m}^2$
Max Height	$\leq 30\text{m}$
Vertical Adjustment	$\leq \pm 3^\circ$
Size	48.3mm
Standard	EN12810 & EN12811

Applications:

Bythai BT03 Ringlock System Scaffolding: The Ideal Solution for Any Building

Bythai BT03 Ringlock System Scaffolding is an ideal solution for many construction projects. It is a modular scaffolding system made from high-grade steel components, designed to ensure high levels of safety and stability. With its vertical and horizontal adjustments of $\pm 3^\circ$ and its components such as vertical, horizontal, diagonal, brace, base plate, ladder, and more, the system is highly versatile and can be customized to fit any construction needs. Bythai BT03 is also EN12810 & EN12811 certified, and comes with a 2-year warranty, so you can be sure that your building projects are constructed with the highest quality and safety standards.

The Bythai BT03 Ringlock System Scaffolding is the perfect solution for any building, and it is especially suitable for ringlock ledger scaffolding and ringlock scaffolding. It is designed to be lightweight and easily assembled, so it is ideal for both indoor and outdoor projects. Moreover, it is incredibly durable and rust-resistant, making it an ideal choice for any construction project. Whether you're building a home, a school, a shopping complex, or any other building, the Bythai BT03 Ringlock System Scaffolding is the perfect solution for your needs.

Customization:

Ringlock System Scaffolding

Brand Name: Bythai

Model Number: BT03

Place of Origin: China

Standard: EN12810 & EN12811

Max Height: ≤30m

Warranty: 2 Years

Size: 48.3mm

Vertical Adjustment: ≤±3°

Bythai Ringlock System Scaffolding provides you the best solution for your projects, with features such as: ringlock standard, ringlock ledger, and other components of the Scaffolding Ringlock System. With the highest quality of EN12810 & EN12811 standard, and a maximum height of 30m, our product is the perfect choice for your needs. Each product comes with a 2 year warranty, and a size of 48.3mm with vertical adjustment of ≤±3°.

Support and Services:

Ringlock System Scaffolding Technical Support and Service

We provide comprehensive technical support and services for our Ringlock System Scaffolding products. Our service team is available to assist you with any technical questions you may have. We provide assistance with installation, maintenance and repair of our products. Our team can help you troubleshoot any technical issues you may encounter and provide advice on how to maintain and extend the life of your Ringlock System Scaffolding. We are also available to provide training and advice on the use of our products. We will work with you to ensure that our products are operating at peak performance and efficiency.

Packing and Shipping:

Packaging and Shipping for Ringlock System Scaffolding

Ringlock system scaffolding should be packaged in accordance with the following instructions:

The scaffolding components must be securely packaged in a cardboard box.

Each box must be clearly labeled with the product name, size, and weight.

The boxes must be sealed with packing tape.

The boxes must be stacked in a secure manner on a pallet.

The pallet must be shrink-wrapped to prevent shifting during transport.

Ringlock system scaffolding should be shipped in accordance with the following instructions:

All shipments must be sent via a shipping company with a reliable delivery record.

The pallet must be clearly labeled with the product name, size, and weight.

A packing list must be included with each shipment.

The shipping company must be notified if the shipment contains hazardous materials.

The delivery address must be clearly marked on the pallet.

FAQ:

Q1: What's the brand name of the Ringlock System Scaffolding?

A1: The brand name of the Ringlock System Scaffolding is Bythai.

Q2: What's the model number of the Ringlock System Scaffolding?

A2: The model number of the Ringlock System Scaffolding is BT03.

Q3: Where is the Ringlock System Scaffolding made?

A3: The Ringlock System Scaffolding is made in China.

Q4: What's the material of the Ringlock System Scaffolding?

A4: The Ringlock System Scaffolding is made of high-strength structural steel.

Q5: What's the loading capacity of the Ringlock System Scaffolding?

A5: The Ringlock System Scaffolding has a loading capacity of up to 4.8KN/m2.



Bythai Scaffolding Co.,Ltd



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605,Industrail Exchange Center ,Huanghua Town Changsha Hunan China