

## Ringlock Scaffolding System with Max Height $\leq 30\text{m}$ and Size 48.3mm

### Our Product Introduction

for more products please visit us on [bythaiscaffold.com](http://bythaiscaffold.com)

#### Basic Information

- Place of Origin: China
- Brand Name: Bythai
- Model Number: BT03



#### Product Specification

- Size: 48.3mm
- Surface Treatment: Hot-dip Galvanized
- Max Height:  $\leq 30\text{m}$
- Warranty: 2 Years
- Material: Q235 Steel
- Joints: Double-locking
- Standard: EN12810 & EN12811
- Weight:  $\leq 30\text{kg/m}^2$
- Highlight: **scaffolding ringlock system,  
horizontal ringlock system scaffolding**

## Product Description

### Product Description:

Ringlock System Scaffolding is a safe and efficient scaffolding product, designed to meet the needs of a wide range of construction projects. Its high-quality galvanized surface treatment provides excellent corrosion resistance, and its 2-year warranty ensures long-term reliability. Its maximum height of up to 30m is ideal for many applications, and its 48.3mm size makes it suitable for a variety of structures. Its double-locking joint system allows for quick and secure assembly, making it a great choice for any building project. Its ringlock design ensures stability and safety, making it an ideal choice for any scaffolding project. Ringlock andamios are the perfect choice for any construction project, offering stability, durability, and safety.

### Features:

Product Name: **Ringlock System Scaffolding**

Horizontal Adjustment:  $\leq \pm 3^\circ$

Standard: **EN12810 & EN12811**

Joints: **Double-locking**

Vertical Adjustment:  $\leq \pm 3^\circ$

Material: **Q235 Steel**

### Technical Parameters:

| Product Attribute        | Value                                                         |
|--------------------------|---------------------------------------------------------------|
| Warranty                 | 2 Years                                                       |
| Horizontal Adjustment    | $\leq \pm 3^\circ$                                            |
| Vertical Adjustment      | $\leq \pm 3^\circ$                                            |
| Safety Factor            | $\geq 4$                                                      |
| Horizontal Load Capacity | $\geq 15\text{KN}$                                            |
| Standard                 | EN12810 & EN12811                                             |
| Surface Treatment        | Hot-dip Galvanized                                            |
| Weight                   | $\leq 30\text{kg/m}^2$                                        |
| Material                 | Q235 Steel                                                    |
| Vertical Load Capacity   | $\geq 45\text{KN}$                                            |
| Keywords                 | Ringlock Scaffolding, Scaffolding Ringlock, Ringlock formwork |

### Applications:

The **Bythai BT03 Ringlock System Scaffolding** is a reliable and efficient solution for any construction and engineering projects. It is made of high quality material and features a **double-locking** joint, vertical load capacity of  $\geq 45\text{KN}$ , and a **maximum height of  $\leq 30\text{m}$** . The entire system is **hot-dip galvanized** to ensure maximum protection against rust and corrosion. It is easy to assemble and disassemble and can be conveniently used in multiple combinations. This product also comes with a **2-year warranty** for added peace of mind. Ideal for all types of construction, the Bythai BT03 Ringlock System Scaffolding is the perfect choice for any Ringlock accessories, Ringlock Scaffolding, and Ringlock andamios.

### Customization:

Bythai Ringlock System Scaffolding

**Brand Name:** Bythai

**Model Number:** BT03

**Place of Origin:** China

**Horizontal Adjustment:**  $\leq \pm 3^\circ$

**Horizontal Load Capacity:**  $\geq 15\text{KN}$

**Components:** Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.

**Safety Factor:**  $\geq 4$

**Vertical Load Capacity:**  $\geq 45\text{KN}$

Bythai Ringlock System Scaffolding is the perfect solution for large-scale and heavy-duty construction projects. This system combines the strength and stability of a Ringlock system with the added security of accessories to provide a safe and secure way to construct a scaffolding. The system features a horizontal adjustment of  $\leq \pm 3^\circ$ , a horizontal load capacity of  $\geq 15\text{KN}$ , and a vertical load capacity of  $\geq 45\text{KN}$ , all with a safety factor of  $\geq 4$ . Components include vertical, horizontal, diagonal, brace, base plate, ladder, and more. With Bythai Ringlock System Scaffolding, you can ensure the safe and successful completion of your project.

## Support and Services:

Ringlock System Scaffolding Technical Support and Service

We offer comprehensive technical support and service for our Ringlock System Scaffolding products.

Our team of experienced engineers is always available to answer questions about installation, use, and maintenance of our scaffolding products. We strive to provide our customers with the highest level of support, and our team is able to troubleshoot any issues that may arise.

We also provide on-site installation and commissioning services to ensure the proper and safe operation of our scaffolding products. Our technicians are highly trained and certified in the use of the Ringlock System Scaffolding and can provide detailed instruction on its proper use.

If you have any questions or need any assistance with our Ringlock System Scaffolding, please do not hesitate to contact us.

## Packing and Shipping:

Packaging and Shipping for Ringlock System Scaffolding

Ringlock System Scaffolding is safely and securely packed to minimize any damage during shipping. It is packed in bundles and wrapped in protective layers of plastic or other materials. All components of the scaffolding are wrapped and labeled to ensure safe delivery to the customer. The scaffolding will be shipped via a reliable carrier to ensure delivery and on-time arrival.

## FAQ:

Ringlock System Scaffolding Q&A

**Q: What is Ringlock System Scaffolding?**

**A:** Ringlock System Scaffolding is a type of scaffolding made of galvanized steel produced by Bythai with model number BT03, which is made in China.

**Q: What are the advantages of Ringlock System Scaffolding?**

**A:** Ringlock System Scaffolding has several advantages, such as easy installation, superior load capacity, high safety and stability, and strong resistance to corrosion.

**Q: What are the main components of Ringlock System Scaffolding?**

**A:** The main components of Ringlock System Scaffolding are standards, ledgers, horizontal braces, diagonal braces, base jack, and scaffolding accessories.

**Q: What is the load capacity of Ringlock System Scaffolding?**

**A:** The load capacity of Ringlock System Scaffolding depends on the configuration and application, but it can reach up to  $4\text{KN}$  per square meter.

**Q: What is the minimum height of Ringlock System Scaffolding?**

**A:** The minimum height of Ringlock System Scaffolding is 1.5 meters.



**Bythai Scaffolding Co.,Ltd**



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605, Industrail Exchange Center ,Huanghua Town Changsha Hunan China